

# T HEAD 419

## ORBITAL WELD HEAD FOR MULTI-PASS GTAW PIPE WELDING


The Magnatech T model weld head is designed to make pipe-to-pipe and pipe-to-fitting welds. It is “full function” – with the capability of reproducing all the motions of a skilled manual welder. The T Head is used for larger diameter/heavy wall applications, requiring the precise weld process control of gas tungsten arc welding. Interchangeable guide rings provide mounting on the pipe, and allow the T Head to cover a broad size range. The T model weld head improves productivity by increasing duty cycle, reducing repair rates, and producing welds of consistent quality.

- Generates high quality welds
- Single or dual wire feeder option
- Rugged design
- State of the art technology

# T HEAD 419

## TORCH OSCILLATION (WEAVE)

Width, speed, and endpoint "dwell" independently programmable. Torch "cross seam" steering electronically controlled using remote pendant. Pulsed current automatically synchronized with torch oscillation.



## 3-AXIS POSITION ADJUSTMENT FOR FILLER WIRE NOZZLE

Multiple adjustments provide precise positioning of filler wire entry into weld puddle.

## WATER-COOLED TORCH

## WELD HEAD MOUNTING/ROTATION

Guide rings attach head to pipe.

## FILLER WIRE SPOOL

Use standard 1 kg (2 lbs) spools.

## HEAD-MOUNTED WIRE FEEDER

Accommodates range of wire diameters.

## SPECIFICATIONS

\*Guide rings come with a one year warranty

|                               |   |
|-------------------------------|---|
| Application                   | Multi-pass orbital GTAW pipe-to-pipe, pipe-to-fitting   |
| Cable length                  | 7.6 m (25') standard. Extension cables available  |
| Pipe (tube) size range        | 168 - 1524 mm (6 - 60") and larger  |
| Filler wire module            | Wire size: 0.8, 0.9, 1.0, 1.2 mm (.030", .035", .040", .045")<br>Max. speed capability: 2540 mm/min. (100 IPM)<br>Spool size: 1 kg (2 lbs) standard. 5 kg (10 lb) spool size optional   |
| Oscillation module            | Max. oscillation stroke amplitude: 16 mm (0.6725")<br>Max. oscillation speed: 1520 mm/min. (60 IPM)<br>Oscillation dwell: 0 - 1 second<br>Cross seam adjustment: ± 6.4 mm (0.25") fine adjustment<br>± 38 mm (1.5") course adjustment |
| Arc gap control module stroke | 66 mm (2.6") stroke. Additional mechanical adjustment allows welding heavier wall pipe  |
| Torch propulsion module       | 250 mm/min. (10 IPM) maximum rotation speed   |
| Water-cooled torch            | 300 A continuous  |
| Torch adjustment capability   | Torch lead/lag adjustment: ± 15 degrees (manual)<br>Torch tilt adjustment: ± 10 degrees (manual)  |
| Power supply compatibility    | Pipemaster 515, Pipemaster 516  |